

PANTAMAT WITH FRONT TO BACK WAIST- BAND TENSIONING



Utility topper with front-to-back waistband tensioning and utility cuff clamps. Suitable for all types of trousers.

Product code: 5309/S

| **Category:** [TENSIONING & TRADITIONAL FINISHERS](#) | **Tags:** [DRYCLEANING](#), [INDUSTRIAL LAUNDRIES](#), [LARGE HOTELS AND COMMUNITY PROFESSIONALS](#), [WETCLEANING](#)

DESCRIZIONE:

Utility topper with front-to-back waistband tensioning and utility cuff clamps. Suitable for all types of trousers.

|

MAIN FEATURES



Full features electronic programmer

Electronic control panel with tensioning parameter controls:

- Easy to use;
- Stores up to ten programs, each one customizable;
- Convenient keys allow to activate or exclude frequently used function;
- Independent adjustment of tensioning of the waist and of the leg.

**Repositionable carriage**

The carriage height can be repositioned to finish trousers with non-standard length such as children's sizes and shorts.

**Utility cuff clamps**

Use the outside-in movement for creased trousers and the inside-out movement for uncreased trousers and fabrics that should not be pressed. May be used for tube skirts.

**Anti-stretch device for waistband and legs**

The anti-stretch feature prevents the fabric from being overstretched during the finishing cycle.

The operator can activate the anti-stretch feature independently for the waistband and the leg length by means of buttons on the console.

**Two pedals operations**

The machine is operated by means of two pedals:

- One to go forward in the cycle (START pedal);
- The other to “undo” any mistakes (BACK pedal).



Front-to-back waist expanders

Designed to concentrate the steam flow on the pleats and pockets area.



Blowing strength adjustment

OPTIONS



Spray group



Pneumatic pleat paddles**TECHNICAL SPECIFICATIONS****5309/S**

Description	Topper with front to back waist- band tensioning
Electrical requirements	400V 3N 50Hz 220V 3 60Hz
Total power	1,1 kW
Steam consumption	20 kg/h
Dimensions	875 x 1160 x 2025 mm 34"x46"80"
Net weight	140 kg